

Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

E-Kleen-SR 152

Product Use

Cleaner

Details of the supplier of the safety data sheet

Electrochemical Products Inc. 17000 West Lincoln Ave New Berlin, WI 53151 Phone: 262-786-9330

Emergency Phone #: NCEC (#EPI-29003) +1 202 464 2554, +44 1865 407333

E-mail: us-sales@epi.com

www.epi.com Fax: 262-786-9403

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Acute Toxicity - Oral - Category 4 Skin Corrosion/Irritation - Category 1 Serious Eye Damage/Eye Irritation - Category 1

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Harmful if swallowed

Causes severe skin burns and eye damage

Precautionary Statement(s)

Prevention



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Wear protective gloves/protective clothing/eye protection/face protection

Wash thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dusts or mists

Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower

Wash contaminated clothing before reuse

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Immediately call a POISON CENTER or doctor

Specific treatment (see label)

Storage

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Statement of Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
7732-18-5	Water	70-75
1310-58-3	Potassium hydroxide	15-20
1312-76-1	Potassium silicate	4-6
527-07-1	Sodium gluconate	2-3
123-91-1	1,4-Dioxane	0.000005
75-21-8	Ethylene oxide	0.00001
61791-14-8	Ethoxylated coconut oil alkyl amine	0.1-0.2

Section 4 - FIRST AID MEASURES

Page 2 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist.

Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation develops or persists, seek medical attention. If skin still feels slippery, caustic maybe still present in large enough quantities to cause rash burn. Continue to wash the affective area until it does not feel slippery.

Eyes

Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. If conscious, drink large quantities of water or acidic beverages like tomato or orange juice or carbonated soft drinks. If vomiting does occur administer additional water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention or advice.

Most Important Symptoms/Effects

Acute

Causes severe irritation or burns to the eyes, skin, gastrointestinal tract, and respiratory system.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide, water fog.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

None identified.

Hazardous Combustion Products

None.

Fire Fighting Measures

Firefighters should wear full protective clothing including self contained breathing apparatus.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Isolate area. Keep unnecessary personnel away. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed.

Page 3 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Methods and Materials for Containment and Cleaning Up

Contain the discharged material. Stop source of leak if possible. Block any potential routes to water systems. Ventilate the contaminated area. Absorb spilled product with a commercial oil absorbent, such as sand or earth. Shovel absorbed material into appropriate container for disposal. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Isolate area. Keep unnecessary personnel away. Follow all Local, State, Federal and Provincial regulations for disposal. Surfaces may become slippery after spillage. Neutralize with dilute acid. Flush spill area with water followed by liberal coverage of sodium bicarbonate.

Environmental Precautions

Do not allow the spilled product to enter public drainage system or open water courses.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Avoid getting this material into contact with your skin and eyes. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up

Keep container tightly closed in a cool, well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Potassium hydroxide	1310-58-3
ACGIH:	2 mg/m3 Ceiling
NIOSH:	2 mg/m3 Ceiling
1,4-Dioxane	123-91-1
ACGIH:	20 ppm TWA
	Skin - potential significant contribution to overall exposure by the cutaneous route
NIOSH:	1 ppm Ceiling 30 min; 3.6 mg/m3 Ceiling 30 min
	500 ppm IDLH
Europe:	20 ppm TWA; 73 mg/m3 TWA

Page 4 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

OSHA (US):	100 ppm TWA; 360 mg/m3 TWA						
	prevent or reduce skin absorption						
Mexico:	25 ppm TWA LMPE-PPT; 90 mg/m3 TWA LMPE-PPT						
	00 ppm STEL [LMPE-CT]; 360 mg/m3 STEL [LMPE-CT]						
	Skin - potential for cutaneous absorption						
Ethylene oxide	75-21-8						
ACGIH:	1 ppm TWA						
NIOSH:	0.1 ppm TWA (less than stated value); 0.18 mg/m3 TWA (less than stated value)						
	5 ppm Ceiling 10 min/day; 9 mg/m3 Ceiling 10 min/day						
	800 ppm IDLH						
OSHA (US):	1 ppm TWA						
	5 ppm Excursion Limit (See 29 CFR 1910.1047) 15 min; 0.5 ppm Action Level (See 29 CFR 1910.1047); 1 ppm TWA (See 29 CFR 1910.1047)						
	5 ppm STEL (See 29 CFR 1910.1047)						
Mexico:	1 ppm TWA LMPE-PPT; 2 mg/m3 TWA LMPE-PPT						

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear chemical goggles; face shield (if splashing is possible).

Skin Protection

Use of protective coveralls and long sleeves is recommended to prevent skin contact. Use of an impervious apron is recommended.

Respiratory Protection

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

Glove Recommendations

Use chemical resistant impervious gloves.

Protective Materials

Eye wash fountain and emergency showers are recommended.



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid	Physical State	Liquid
Odor	Characteristic	Color	Not available
Odor Threshold	Not available	рН	13 - 14
Melting Point	Not available	Boiling Point	>214 °F (101 °C)
Freezing point	45 - 50 °F (7.22-10 °C)	Evaporation Rate	Not available
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	1.2 - 1.22
Water Solubility	Completely	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	Not available	VOC	0

Section 10 - STABILITY AND REACTIVITY

Reactivity

Contact with some metals, particularly magnesium, aluminum,zinc (galvanized) can rapidly generate hydrogen which can be explosive.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Will not occur.

Conditions to Avoid

Page 6 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Avoid contact with extreme heat. Avoid contact with acids.

Incompatible Materials

This product may react with strong acids.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition products

Upon thermal decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Section 11 - TOXICOLOGICAL INFORMATION

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Water (7732-18-5)

Oral LD50 Rat >90 mL/kg

Potassium hydroxide (1310-58-3)

Oral LD50 Rat 284 mg/kg

Potassium silicate (1312-76-1)

Oral LD50 Rat 1300 mg/kg

1,4-Dioxane (123-91-1)

Oral LD50 Rat 5170 mg/kg

Dermal LD50 Rabbit 7600 µL/kg

Inhalation LC50 Rat 46 mg/L 2 h

Ethylene oxide (75-21-8)

Oral LD50 Rat 72 mg/kg

Inhalation LC50 Rat 800 ppm 4 h

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

No data available.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

Page 7 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

1,4- Dioxane	123-91-1
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 71 [1999]; Supplement 7 [1987]; Monograph 11 [1976] (Group 2B (possibly carcinogenic to humans))
NTP:	Reasonably Anticipated To Be A Human Carcinogen
DFG:	Category 4 (no significant contribution to human cancer)
OSHA:	Present
Ethylene oxide	75-21-8
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100F [2012]; Monograph 97 [2008]; Monograph 60 [1994] (overall evaluation upgraded from Group 2A to Group 1 based on mechanistic and other relevant data) (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen
DFG:	Category 2 (considered to be carcinogenic for man)
OSHA:	Present
OSHA:	see 29 CFR 1910.1047

Germ Cell Mutagenicity

No data available.

Tumorigenic Data

No data available

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Repeated Exposure

No data available.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Page 8 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Because of the high pH of this product, it would be expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Component Analysis - Aquatic Toxicity

component Analysis - Aquatic Toxicity					
Potassium silicate	1312-76-1				
Fish:	LC50 96 h Lepomis macrochirus 301 - 478 mg/L; LC50 96 h Brachydanio rerio 3185 mg/L [semi-static]				
1,4-Dioxane	123-91-1				
Fish:	LC50 96 h Lepomis macrochirus >10000 mg/L [static]; LC50 96 h Lepomis macrochirus >10000 mg/L [semi-static]; LC50 96 h Pimephales promelas 9850 mg/L [flow-through]; LC50 96 h Pimephales promelas 10306 - 14742 mg/L [static]; LC50 96 h Pimephales promelas 9850 mg/L				
Invertebrate:	EC50 48 h water flea 163 mg/L [static]				
Ethylene oxide	75-21-8				
Fish:	LC50 96 h Pimephales promelas 73 - 96 mg/L				
Invertebrate:	LC50 48 h Daphnia magna 137 - 300 mg/L IUCLID				

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

As shipped, this product would be considered a D002 (corrosive) waste. The U.S. EPA has not published waste numbers for this product's components. Waste must be handled in accordance with all federal, state, provincial, and local regulations. In case of large spills, follow all facility Emergency Response Procedures. Do not allow this material to into sewers/water supplies. Do not reuse container. Dispose of container and any unused contents in accordance with Federal, State, Provincial and Local Waste Regulations.

Section 14 - TRANSPORT INFORMATION

Page 9 of 13 Issue date: 2016-09-30 Revision 2.0 Print date: 2016-09-30



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

US DOT Information:

Shipping Name: Potassium hydroxide, solution

Hazard Class: 8 UN/NA #: UN1814 Packing Group: II

Required Label(s): Corrosive

TDG Information:

Shipping Name: Potassium hydroxide, solution

Hazard Class: 8 UN#: UN1814 Packing Group: II

Required Label(s): Corrosive

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Potassium hydroxide	1310-58-3
CERCLA:	1000 lb final RQ; 454 kg final RQ
1,4-Dioxane	123-91-1
SARA 313:	0.1 % de minimis concentration
CERCLA:	100 lb final RQ; 45.4 kg final RQ
Ethylene oxide	75-21-8
SARA 302:	1000 lb TPQ
SARA 313:	0.1 % de minimis concentration
CERCLA:	10 lb final RQ; 4.54 kg final RQ
OSHA (safety):	5000 lb TQ
SARA 304:	10 lb EPCRA RQ

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

Potassium hydroxide	1310-58-3	Yes	Yes	Yes	Yes	Yes
1,4-Dioxane	123-91-1	Yes	Yes	Yes	Yes	Yes
Ethylene oxide	75-21-8	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

1,4-Dioxane	123-91-1
Carc:	carcinogen, 1/1/1988
Ethylene oxide	75-21-8
Carc:	carcinogen, 7/1/1987
Repro/Dev. Tox	developmental toxicity, 8/7/2009
	male reproductive toxicity, 8/7/09
	female reproductive toxicity, initial date 2/27/87

Canada Regulations

This material is a controlled product under Canadian WHMIS regulations.

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Potassium hydroxide	1310-58-3		
	1 %		
1,4-Dioxane	123-91-1		
	0.1 %		
Ethylene oxide	75-21-8		
	0.1 %		

Component Analysis - Inventory

Water (7732-18-5)



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Potassium hydroxide (1310-58-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Potassium silicate (1312-76-1)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Sodium gluconate (527-07-1)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

1,4-Dioxane (123-91-1)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Ethylene oxide (75-21-8)

U	S	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Y	es	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 3 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard



Material Name: E-Kleen-SR 152 SDS ID: EPI-0300c

NFPA Ratings

Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU -European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; ICAO - International Civil Aviation Organization; IDL -Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; JP - Japan; Kow -Octanol/water partition coefficient; KECI - Korea Existing Chemicals Inventory; KECL - Korea Existing Chemicals List; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH-Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA -Korea Toxic Chemicals Control Act,; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

Reasonable care has been taken in the preparation of this information; however, the manufacturer makes no warranty whatsoever including the warranty of merchantability, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental, consequential, or other such damages resulting from its use or misuse...