SAFETY DATA SHEET



Revision date 23-May-2022

Revision Number 1

1. Identification

Product identifier

Product Name E-Tec 505+

Other means of identification

Product Code(s) EPI-0057C

Synonyms None

Details of the supplier of the safety data sheet

Manufacturer Address

Electrochemical Products Inc. 17000 West Lincoln Ave New Berlin, WI 53151 Phone: 262-786-9330 E-mail: us-sales@epi.com

www.epi.com Fax: 262-786-9403

Emergency telephone number

Emergency Telephone NCEC (#EPI-29003) +1 202 464 2554, +44 1865 407333

2. Hazard(s) identification

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Flammable liquids	Category 3

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Harmful if inhaled

May cause genetic defects

May cause cancer

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Appearance Amber liquid Physical state Liquid Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown acute toxicity

Other information

May be harmful in contact with skin. Causes mild skin irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No	Weight-%	Trade secret
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	65-85	*
Distillates, petroleum, hydrotreated heavy	64742-52-5	5-10	*
naphthenic			
Benzene, 1,2,4-trimethyl-	95-63-6	3-7	*

Xylenes (o-, m-, p- isomers)	1330-20-7	3-7	*
Calcium Sulfonate	Trade secret	1-5	*
Ethylbenzene	100-41-4	0.1-1	*
Cumene	98-82-8	0.1-1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. Immediate medical attention is required.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed

pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid breathing vapors

or mists.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause

redness and irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media

Large Fire

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire

extinguishing water must be disposed of in accordance with local regulations.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge

Yes.

Special protective equipment for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing

vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Distillates, petroleum,	TWA: 5 mg/m³ inhalable	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³
hydrotreated heavy naphthenic	particulate matter excluding	(vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³
64742-52-5	metal working fluids, highly &		STEL: 10 mg/m ³
	severely refined		-
Benzene, 1,2,4-trimethyl-	TWA: 25 ppm	(vacated) TWA: 25 ppm	TWA: 25 ppm
95-63-6		(vacated) TWA: 125 mg/m ³	TWA: 125 mg/m ³
Xylenes (o-, m-, p- isomers)	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	
Cumene	TWA: 5 ppm	TWA: 50 ppm	IDLH: 900 ppm
98-82-8		TWA: 245 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 245 mg/m ³
		(vacated) TWA: 245 mg/m ³	
		(vacated) S*	
		S*	

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid Appearance Amber liquid

EPI-0057C - **E-Tec 505+ Revision date** 23-May-2022

Color No information available

Odor Solvent

Property Values Remarks • Method

Hq No data available None known No data available None known Melting point / freezing point 157 °C / 314.6 °F Boiling point / boiling range None known 52.2 °C / 126 °F Flash point None known Relative density 0.805 0.84 None known Water solubility Insoluble in water None known

Other information

VOC Content (%) 636 g/L

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on

components).

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes mild skin irritation. May be harmful in contact

with skin.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause

redness and irritation.

Acute toxicity

Numerical measures of toxicity

No information available

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 12,783.20 mg/kg

EPI-0057C - E-Tec 505+

•

ATEmix (dermal) 3,732.30 mg/kg ATEmix (inhalation-dust/mist) 1.66 mg/l

Unknown acute toxicity

Component Information

John Poriorit Information			
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Benzene, 1,2,4-trimethyl- 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Calcium Sulfonate	> 20 g/kg(Rat)	> 5000 mg/kg (Rabbit)	> 1.9 mg/L (Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 μL/kg (Rabbit)	> 3577 ppm (Rat) 6 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for

ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	-	Group 1	Known	X
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	-	Group 2B	-	Х
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	Х

Legend

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Target organ effects Respiratory system, Eyes, Skin, Central nervous system, Blood.

Aspiration hazard May be fatal if swallowed and enters airways.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Solvent naphtha,	EC50: =450mg/L (96h,	LC50: =800mg/L (96h,	-	EC50: >100mg/L (48h,
petroleum, medium	Pseudokirchneriella	Pimephales promelas)		Daphnia magna)
aliphatic	subcapitata)			
64742-88-7				
Distillates, petroleum,	-	LC50: >5000mg/L (96h,	-	EC50: >1000mg/L (48h,
hydrotreated heavy		Oncorhynchus mykiss)		Daphnia magna)
naphthenic				
64742-52-5				
Benzene, 1,2,4-trimethyl-	-	LC50: 7.19 - 8.28mg/L	-	EC50: =6.14mg/L (48h,
95-63-6		(96h, Pimephales		Daphnia magna)
		promelas)		
		LC50: =7.72mg/L (96h,		
		Pimephales promelas)		
Xylenes (o-, m-, p-	EC50: =11mg/L (72h,	LC50: 13.1 - 16.5mg/L	-	LC50: =0.6mg/L (48h,
isomers)	Pseudokirchneriella	(96h, Lepomis		Gammarus lacustris)
1330-20-7	subcapitata)	macrochirus)		EC50: =3.82mg/L (48h,
		LC50: 13.5 - 17.3mg/L		water flea)
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 2.661 - 4.093mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 23.53 - 29.97mg/L		
		(96h, Pimephales		
		promelas)		
		LC50: 30.26 - 40.75mg/L		
		(96h, Poecilia reticulata)		
		LC50: 7.711 - 9.591mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =13.4mg/L (96h,		
		Pimephales promelas)		
		LC50: =19mg/L (96h,		

		Lepomis macrochirus)		
		LC50: =780mg/L (96h,		
		Cyprinus carpio)		
		LC50: >780mg/L (96h,		
		Cyprinus carpio)		
Calcium Sulfonate	-	LC50: 5.7 - 9.7mg/L (96h,	-	EC50: 6.2 - 12mg/L (48h,
		Pimephales promelas)		Daphnia magna)
		LC50: 1.0 - 10.0mg/L		
		(96h, Pimephales		
		promelas)		
Ethylbenzene	EC50: 1.7 - 7.6mg/L	LC50: 11.0 - 18.0mg/L	-	EC50: 1.8 - 2.4mg/L
100-41-4	(96h, Pseudokirchneriella	(96h, Oncorhynchus		(48h, Daphnia magna)
	subcapitata)	mykiss)		
	EC50: 2.6 - 11.3mg/L	LC50: 7.55 - 11mg/L		
	(72h, Pseudokirchneriella	(96h, Pimephales		
	subcapitata)	promelas)		
	EC50: =11mg/L (72h,	LC50: 9.1 - 15.6mg/L		
	Pseudokirchneriella	(96h, Pimephales		
	subcapitata)	promelas)		
	EC50: =4.6mg/L (72h,	LC50: =32mg/L (96h,		
	Pseudokirchneriella	Lepomis macrochirus)		
	subcapitata)	LC50: =4.2mg/L (96h,		
	EC50: >438mg/L (96h,	Oncorhynchus mykiss)		
	Pseudokirchneriella	LC50: =9.6mg/L (96h,		
	subcapitata)	Poecilia reticulata)		
Cumene	EC50: =2.6mg/L (72h,	LC50: 6.04 - 6.61mg/L	-	EC50: 7.9 - 14.1mg/L
98-82-8	Pseudokirchneriella	(96h, Pimephales		(48h, Daphnia magna)
	subcapitata)	promelas)		EC50: =0.6mg/L (48h,
		LC50: =2.7mg/L (96h,		Daphnia magna)
		Oncorhynchus mykiss)		
		LC50: =4.8mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: =5.1mg/L (96h,		
		Poecilia reticulata)		

Persistence and degradability

No information available.

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient
Benzene, 1,2,4-trimethyl-	3.63
95-63-6	
Xylenes (o-, m-, p- isomers)	2.77 - 3.15
1330-20-7	
Ethylbenzene	3.2
100-41-4	
Cumene	3.7
98-82-8	

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Revision date 23-May-2022

EPI-0057C - E-Tec 505+

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number U055 U239

14. Transport information

Contaminated packaging

DOT Not regulated

TDG

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es) 3
Packing group |||

Special Provisions 91, 92, 150

Description UN1268, Petroleum distillates, n.o.s., 3, III

MEX

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es) 3
Packing group

Description UN1268, Petroleum distillates, n.o.s., 3, III

Special Provisions 223

ICAO (air)

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es) 3
Packing group III

Description UN1268, Petroleum distillates, n.o.s., 3, III

Special Provisions A3

<u>IATA</u>

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es) 3
Packing group ||||

Description UN1268, Petroleum distillates, n.o.s., 3, III

Special Provisions A3 ERG Code 3L

<u>IMDG</u>

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es)

Packing group

EmS-No

Special Provisions

Marine pollutant

S

3

III

F-E, S-E

223, 955

Description UN1268, Petroleum distillates, n.o.s., 3, III, (52.2°C c.c.)

RID

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es) 3
Packing group III
Classification code F1

Description UN1268, Petroleum distillates, n.o.s., 3, III

<u>ADR</u>

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

•

Transport hazard class(es)

Packing group

Classification code

Tunnel restriction code

Special Provisions

3

III

(D/E)

664

Description UN1268, Petroleum distillates, n.o.s., 3, III, (D/E)

ADN

UN number or ID number UN1268

UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es) 3
Packing group III
Classification code F1

Description UN1268, Petroleum distillates, n.o.s., 3, III

Ventilation VE01 Equipment Requirements PP, EX, A

15. Regulatory information

International Inventories

TSCA Complies

Chemical name	CAS No	US TSCA Inventory listing	US TSCA inactive/active designation
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	Present	Active
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	Present	Active
Benzene, 1,2,4-trimethyl-	95-63-6	Present	Active
Xylenes (o-, m-, p- isomers)	1330-20-7	Present	Active
Calcium Sulfonate	-	Present	Active
Ethylbenzene	100-41-4	Present	Active
Cumene	98-82-8	Present	Active

DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Does not comply
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Revision date 23-May-2022

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylenes (o-, m-, p- isomers)	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ
Cumene	5000 lb	-	RQ 5000 lb final RQ
98-82-8			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Distillates, petroleum,	Х	-	X
hydrotreated heavy naphthenic 64742-52-5			
Benzene, 1,2,4-trimethyl- 95-63-6	X	-	Х
Xylenes (o-, m-, p- isomers) 1330-20-7	X	-	X
Ethylbenzene 100-41-4	X	-	Х
Cumene 98-82-8	X	-	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA
HMISHealth hazards3Flammability2Instability0Special hazards-Chronic Hazard Star Legend*= Chronic Health Hazard*= Chronic Health Hazard*= Chronic Health Hazard*= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

·

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date 23-May-2022

Revision NoteNo information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet