

SAFETY DATA SHEET



Revision date 23-May-2022

Revision Number 1

1. Identification

Product identifier

Product Name E-Tec 502

Other means of identification

Product Code(s) EPI-0052C

Synonyms None

Details of the supplier of the safety data sheet

Manufacturer Address

Electrochemical Products Inc.
17000 West Lincoln Ave
New Berlin, WI 53151
Phone: 262-786-9330
E-mail: us-sales@epi.com
www.epi.com
Fax: 262-786-9403

Emergency telephone number

Emergency Telephone NCEC (#EPI-29003) +1 202 464 2554, +44 1865 407333

2. Hazard(s) identification

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Flammable liquids	Category 3

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Harmful if inhaled
May cause genetic defects
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Appearance** Amber liquid**Physical state** Liquid**Odor** Solvent**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
 Call a POISON CENTER or doctor if you feel unwell
 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown acute toxicity**Other information**

May be harmful in contact with skin. Causes mild skin irritation. Harmful to aquatic life. May cause long lasting harmful effects to aquatic life. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Trade secret
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	69-71	*
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	12-16	*
Calcium Sulfonate	Trade secret	6-9	*

Benzene, 1,2,4-trimethyl-	95-63-6	2-2.5	*
Xylenes (o-, m-, p- isomers)	1330-20-7	1-1.9	*
Ethylbenzene	100-41-4	0.2-0.4	*
Cumene	98-82-8	0.2-0.4	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	---

5. Fire-fighting measures

Suitable Extinguishing Media Large Fire	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Explosion data Sensitivity to mechanical impact	None.

Sensitivity to static discharge Yes.

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	TWA: 5 mg/m ³ inhalable particulate matter excluding metal working fluids, highly & severely refined	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³	IDLH: 2500 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Cumene 98-82-8	TWA: 5 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
 Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state Liquid
Appearance Amber liquid

Color amber
Odor Solvent

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	157 °C / 314.6 °F	None known
Flash point	52.2 °C / 126 °F	None known
Relative density	0.81 - 0.83	None known
Water solubility	Insoluble in water	None known

Other information

VOC Content (%) 738 g/L

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information**Information on likely routes of exposure****Product Information**

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes mild skin irritation. May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.

Acute toxicity**Numerical measures of toxicity**

No information available

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 12,388.60 mg/kg

ATEmix (dermal) 3,999.30 mg/kg
ATEmix (inhalation-dust/mist) 1.76 mg/l

Unknown acute toxicity**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Calcium Sulfonate	> 20 g/kg (Rat)	> 5000 mg/kg (Rabbit)	> 1.9 mg/L (Rat) 4 h
Benzene, 1,2,4-trimethyl- 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	-	Group 1	Known	X
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	-	Group 2B	-	X
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X

Legend**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Target organ effects	Respiratory system, Eyes, Skin, Central nervous system, Blood.
Aspiration hazard	May be fatal if swallowed and enters airways.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	EC50: =450mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =800mg/L (96h, Pimephales promelas)	-	EC50: >100mg/L (48h, Daphnia magna)
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
Calcium Sulfonate	-	LC50: 5.7 - 9.7mg/L (96h, Pimephales promelas) LC50: 1.0 - 10.0mg/L (96h, Pimephales promelas)	-	EC50: 6.2 - 12mg/L (48h, Daphnia magna)
Benzene, 1,2,4-trimethyl- 95-63-6	-	LC50: 7.19 - 8.28mg/L (96h, Pimephales promelas) LC50: =7.72mg/L (96h, Pimephales promelas)	-	EC50: =6.14mg/L (48h, Daphnia magna)
Xylenes (o-, m-, p-isomers) 1330-20-7	EC50: =11mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	LC50: =0.6mg/L (48h, Gammarus lacustris) EC50: =3.82mg/L (48h, water flea)

		LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: =13.4mg/L (96h, Pimephales promelas) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio)		
Ethylbenzene 100-41-4	EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: =11mg/L (72h, Pseudokirchneriella subcapitata) EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: =9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
Cumene 98-82-8	EC50: =2.6mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: =4.8mg/L (96h, Oncorhynchus mykiss) LC50: =5.1mg/L (96h, Poecilia reticulata)	-	EC50: 7.9 - 14.1mg/L (48h, Daphnia magna) EC50: =0.6mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Benzene, 1,2,4-trimethyl- 95-63-6	3.63
Xylenes (o-, m-, p- isomers) 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.2
Cumene 98-82-8	3.7

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. Transport information

DOT Not regulated

TDG

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.
Transport hazard class(es) 3
Packing group III
Special Provisions 91, 92, 150
Description UN1268, Petroleum distillates, n.o.s., 3, III

MEX

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.
Transport hazard class(es) 3
Packing group III
Description UN1268, Petroleum distillates, n.o.s., 3, III
Special Provisions 223

ICAO (air)

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.
Transport hazard class(es) 3
Packing group III
Description UN1268, Petroleum distillates, n.o.s., 3, III
Special Provisions A3

IATA

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.
Transport hazard class(es) 3
Packing group III
Description UN1268, Petroleum distillates, n.o.s., 3, III
Special Provisions A3
ERG Code 3L

IMDG

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.
Transport hazard class(es) 3
Packing group III
EmS-No F-E, S-E
Special Provisions 223, 955
Marine pollutant NP
Description UN1268, Petroleum distillates, n.o.s., 3, III, (52.2°C c.c.)

RID

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.
Transport hazard class(es) 3
Packing group III
Classification code F1
Description UN1268, Petroleum distillates, n.o.s., 3, III

ADR

UN number or ID number UN1268
UN proper shipping name Petroleum distillates, n.o.s.

Transport hazard class(es)	3
Packing group	III
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	664
Description	UN1268, Petroleum distillates, n.o.s., 3, III, (D/E)

ADN

UN number or ID number	UN1268
UN proper shipping name	Petroleum distillates, n.o.s.
Transport hazard class(es)	3
Packing group	III
Classification code	F1
Description	UN1268, Petroleum distillates, n.o.s., 3, III
Ventilation	VE01
Equipment Requirements	PP, EX, A

15. Regulatory information**International Inventories**

TSCA Complies

Chemical name	CAS No	US TSCA Inventory listing	US TSCA inactive/active designation
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	Present	Active
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	Present	Active
Calcium Sulfonate	-	Present	Active
Benzene, 1,2,4-trimethyl-	95-63-6	Present	Active
Xylenes (o-, m-, p- isomers)	1330-20-7	Present	Active
Ethylbenzene	100-41-4	Present	Active
Cumene	98-82-8	Present	Active

DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	X	-	X
Benzene, 1,2,4-trimethyl- 95-63-6	X	-	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X	-	X
Ethylbenzene 100-41-4	X	-	X
Cumene 98-82-8	X	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 3	Flammability 2	Instability 0	Special hazards -
HMIS	Health hazards 2 *	Flammability 2	Physical hazards 0	Personal protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

TWA Ceiling	TWA (time-weighted average) Maximum limit value	STEL *	STEL (Short Term Exposure Limit) Skin designation
----------------	--	-----------	--

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 23-May-2022
Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet