

E-Tec™ 527

Temporary Rust Inhibitor for Steel

E-Tec 527 is a mild water based composition formulated to provide temporary rust protection for steel surfaces when stored indoors. It leaves a dry, invisible film which will not affect subsequent operations. Excellent for protecting steel surfaces while in process of manufacture. It does provide some mild cleaning action and can be used in tumbling or burnishing operations to prevent rapid oxidation of steel surfaces.

APPLICATION

E-Tec 527 is used at one (1) to four (4) fluid ounces per gallon of water, and temperatures from 65°F to 180°F. Elevated temperatures facilitate drying. The higher the concentration the greater the protection. The strength of the solution is maintained by periodic additions of **E-Tec 527** concentrate. The solution should be discarded when it becomes contaminated with soils.

The solution does not have to be ventilated. Tanks and heaters may be constructed of mild steel.

E-Tec 527 is non-toxic and is essentially non-hazardous, and does not require special clothing, etc. However, it is recommended that eye protection be worn while preparing the solution and working with the solution.

PACKAGING

One (1), 5 and 55 gallon non-returnable containers.

IMPORTANT NOTICE! For Industrial Use Only

The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: seller's and manufacturers only obligation shall be to replace such quantity of the product as proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. **Neither seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use or the inability to use the product.**

8/5/97