



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

E-Kleen 148-B

Product Use

Alkaline cleaner

Manufacturer Information

Electrochemical Products Inc.
17000 West Lincoln Ave
New Berlin, WI 53151
Phone: 262-786-9330
Emergency Phone #: Chemtrec #800-424-9300 (CCN7498)
E-mail: us-sales@epi.com
www.epi.com
Fax: 262-786-9403

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Skin Corrosion/Irritation - Category 1
Serious Eye Damage/Eye Irritation - Category 1

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Causes severe skin burns and eye damage

Precautionary Statement(s)

Prevention



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Wear protective gloves/protective clothing/eye protection/face protection
Wash thoroughly after handling
Do not breathe dusts or mists

Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
Immediately call a POISON CENTER or doctor
Specific treatment (see label)

Storage

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
7732-18-5	Water	60-100
1344-09-8	Sodium silicate	8-15
Trade Secret	Borate Compound	1-10
7758-29-4	Pentasodium triphosphate	1-5
1310-58-3	Potassium hydroxide	1-5
527-07-1	Sodium gluconate	0-1

Section 4 - FIRST AID MEASURES

Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist.

Skin



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation develops or persists, seek medical attention. If skin still feels slippery, caustic maybe still present in large enough quantities to cause rash burn. Continue to wash the affective area until it does not feel slippery.

Eyes

Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. If conscious, drink large quantities of water or acidic beverages like tomato or orange juice or carbonated soft drinks. If vomiting does occur administer additional water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention or advice.

Most Important Symptoms/Effects

Acute

Causes severe irritation or burns to the eyes, skin, gastrointestinal tract, and respiratory system.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide, water fog.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Contact with some metals, particularly magnesium, aluminum, zinc (galvanized) can rapidly generate hydrogen which can be explosive.

Hazardous Combustion Products

None.

Fire Fighting Measures

Firefighters should wear full protective clothing including self contained breathing apparatus.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this SDS. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed.



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Methods and Materials for Containment and Cleaning Up

Isolate area. Keep unnecessary personnel away. Contain the discharged material. Stop source of leak if possible. Block any potential routes to water systems. Ventilate the contaminated area. Absorb spilled product with a commercial oil absorbent, such as sand or earth. Shovel absorbed material into appropriate container for disposal. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Isolate area. Keep unnecessary personnel away. Follow all Local, State, Federal and Provincial regulations for disposal. Surfaces may become slippery after spillage. Neutralize with dilute acid. Flush spill area with water followed by liberal coverage of sodium bicarbonate.

Environmental Precautions

Do not allow the spilled product to enter public drainage system or open water courses.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Avoid getting this material into contact with your skin and eyes. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up

Keep container tightly closed in a cool, well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Potassium hydroxide	1310-58-3
ACGIH:	2 mg/m ³ Ceiling
NIOSH:	2 mg/m ³ Ceiling

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear chemical goggles; face shield (if splashing is possible).

Skin Protection

Use of protective coveralls and long sleeves is recommended to prevent skin contact. Use of an impervious apron is recommended.



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Respiratory Protection

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

Glove Recommendations

Use chemical resistant impervious gloves.

Protective Materials

Eye wash fountain and emergency showers are recommended.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid	Physical State	Liquid
Odor	Characteristic	Color	Dark Brown
Odor Threshold	Not available	pH	11.5 - 13
Melting Point	Not available	Boiling Point	>214 °F (101 °C)
Freezing point	45 - 50 °F (7.22-10 °C)	Evaporation Rate	Not available
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	1.15 - 1.2
Water Solubility	Completely	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	Not available	VOC	0

Section 10 - STABILITY AND REACTIVITY



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Reactivity

No known hazardous reactions.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Will not occur.

Conditions to Avoid

Avoid contact with extreme heat.

Incompatible Materials

This product may react with strong acids.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition products

Upon thermal decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Section 11 - TOXICOLOGICAL INFORMATION

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Water (7732-18-5)

Oral LD50Rat >90 mL/kg

Sodium silicate (1344-09-8)

Oral LD50Rat 1960 mg/kg

Pentasodium triphosphate (7758-29-4)

Oral LD50Rat 3120 mg/kg

Dermal LD50Rabbit >7940 mg/kg

Potassium hydroxide (1310-58-3)

Oral LD50Rat 284 mg/kg

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

No data available.

Respiratory Sensitization

No data available.



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Dermal Sensitization

No data available.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Repeated Exposure

No data available.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Because of the high pH of this product, it would be expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Component Analysis - Aquatic Toxicity

Sodium silicate	1344-09-8
Fish:	LC50 96 h Lepomis macrochirus 301 - 478 mg/L; LC50 96 h Brachydanio rerio 3185 mg/L [semi-static]

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

The U.S. EPA has not published waste numbers for this product's components. Waste must be handled in accordance with all federal, state, provincial, and local regulations. In case of large spills, follow all facility Emergency Response Procedures. Do not allow this material to into sewers/water supplies. Do not reuse container. Dispose of container and any unused contents in accordance with Federal, State, Provincial and Local Waste Regulations.



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: Potassium hydroxide, solution

Hazard Class: 8

UN/NA #: UN1814

Packing Group: II

Required Label(s): Corrosive

TDG Information:

Shipping Name: Potassium hydroxide, solution

Hazard Class: 8

UN#: UN1814

Packing Group: II

Required Label(s): Corrosive

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Potassium hydroxide	1310-58-3
CERCLA:	1000 lbfinal RQ; 454 kgfinal RQ

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Pentasodium triphosphate	7758-29-4	Yes	Yes	No	No	Yes
Potassium hydroxide	1310-58-3	Yes	Yes	Yes	Yes	Yes

Not listed under California Proposition 65

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

Potassium hydroxide	1310-58-3
	1 %

Component Analysis - Inventory

Water (7732-18-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Sodium silicate (1344-09-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Pentasodium triphosphate (7758-29-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Potassium hydroxide (1310-58-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Sodium gluconate (527-07-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard



Safety Data Sheet

Material Name: E-Kleen 148-B

SDS ID: EPI-0107c

NFPA Ratings

Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.